

## HYDRAULIC PUMP DRIVES PRODUCT SPECIFICATION FORM

**ROTATION APPLICATIONS** 

## **CONTACT INFORMATION**

FIRST NAME: LAST NAME:		DATE:					
COMPANY NAME:	EMAIL:			PHON	E NUMBE	R·	
COMPANT NAME.	EWAIL:				LIVOWIDE	14.	
PROJECT NAME:	ANNUAL USAGE:			]			
INPUT							
○ CLUTCH—— мо	DEL:	SAE	SIZE:				
GEAR — SPECIFY SIZE:					INPU	T SPEED:	
O PLATE — DIA	METER:	SAE	SIZE:				
RUBBER BLOCK ———— SPECIFY SIZE:					HOR	SEPOWER	:
SHAFT————————————————————————————————————							
O TORSIONAL COUPLING — DIA	METER:	SAE	SIZE:				
GEAR RATIO: U = SPEED INCREASER D = SPEED REDUCER  Note: Refer to selected model for available gear ratios.							
OUTPUT		I	I	I	ı	I	ı
NUMBER OF PADS:		PAD "A"	PAD "B"	PAD "C"	PAD "D"	PAD "E"	PAD "F"
	SAE FLANGE BOLTS	2-BOLT				4-BOLT	4-BOLT
Note: Not all Flange, Bolt and Spline combinations are available. Check	SAE SPLINE	2-0011				4-0021	7-0011
with the pump manufacturer or a TWG representative for availability.	HP (MAX)						
ADDITIONAL SPECIFICATIONS	D O F	E	(A) (B) (C) (C) (C) (C) (C) (C) (C) (C) (C) (C	E	A B	D	

TWG USE ONLY

**SUBMITTED BY: APPROVED BY: ER NUMBER:**